


Ohm and Current Meter Milli-TO 3

for measurement of volume, surface, bleeder resistance, small currents and cable resistance according standards DIN, EN, IEC and ASTM



- ▶ resistance range from 1×10^{-5} resolution to 1.6×10^{15} Ohm
- ▶ current range from 0.01 pA resolution to 1.1 mA
- ▶ autoranging or manual ranging
- ▶ easy handling by predefined buttons
- ▶ variable test voltage from 1 to 500 V
- ▶ limit indication by relay and beeper
- ▶ compensation of thermo voltage in low ohm range
- ▶ zero control
- ▶ variable timer from 10 to 300 sec
- ▶ RS 232 interface
- ▶ measurement rate: approx. 1 per sec
- ▶ 2 LCD displays
- ▶ dimensions in mm: 340 x 150 x 300
- ▶ weight: 5,7 kg

Accessories:

- wide range of electrodes
- measurement cables
- resistors for calibration
- High-Ohm shield chambers

The high-precision instrument Milli-TO 3 is a refinement of the Milli-TO 2, which was manufactured and sold with great success for over 20 years.


The Milli-TO 3 identifies resistance values from 10 μ Ohm resolution up to 1,6 PetaOhm full scale easily and reliable.

To handle the instrument you can choose between an internal menu or a PC-GUI. The Milli-TO 3 provides a programmable and remote-controlled interface which also allows processing all measured data.

The measured values are displayed in scientific form with $2\frac{1}{2}$ to $4\frac{1}{2}$ digits.

You can choose between 3 predefined test voltages of 10 V, 100 V or 500 V or a variable voltage range, programmable from 1 V to 500 V in 1 V steps.

The test voltage source has a low capacitance and the max. test current is < 3 mA.



Milli-TO 3 with optional electrode HOW 3



Milli-TO 3 with optional electrode EH 15/20